



Transmax Agri MP Plus 20W-40

Super Universal Tractor Oil

Description

Castrol Transmax Agri MP Plus 20W-40 is a quality multi-purpose oil suitable for use in a wide range of applications on the farm. It has been developed specifically to deliver performance and protection for engines, transmissions, wet brakes, hydraulics and front axles.

Advantages

- One oil simplified servicing, avoids misapplication.
- One oil reduces inventory, saves money.
- Improved wear protection in latest generation diesel engines.
- It has significantly enhanced soot handling performance.

Typical Characteristics

Name	Method	Units	Transmax Agri MP Plus 20W-40
Density @ 15C, Relative	ASTM D1298	g/ml	0.894
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.8
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	124
Viscosity Index	ASTM D2270	None	109
Viscosity, CCS -15C	ASTM D5293	mPa.s (cP)	8950
Viscosity, Brookfield @ -18C	ASTM D2983	mPa.s (cP)	19200
Pour Point	ASTM D97	°C	-36
Flash Point, COC	ASTM D92	°C	264

Product Performance Claims

API GL-4
API CE/SF

Transmax Agri MP Plus 20W-40
11 Nov 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890
www.castrol.com.au www.msds.castrol.com.au