



TRANSMAX Universal 80W-90

Universal Fluid for manual transmissions and axles

Description

Castrol TRANSMAX Universal 80W-90 is a multipurpose gear lubricant for use in both synchronised manual transmissions and final drives and differentials where either API GL-4 or API GL-5 are specified.

Advantages

- A single product for transmissions and final drives reducing inventory and the potential for misapplication.
- High temperature stability gives superior performance and extended drain potential.
- Optimised synchroniser performance gives smooth gear shifting at all temperatures.
- Excellent wear protection extends component life and reduces maintenance costs.

Typical Characteristics

Name	Method	Units	Transmax Universal 80W-90
Density @ 15C, Relative	ASTM D4052	g/ml	0.88
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	15.6
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	106
Viscosity Index	ASTM D2270	None	156
Viscosity, Brookfield @ -26C (80W)	ASTM D2983	mPa.s (cP)	21000
Pour Point	ASTM D97	°C	-42

Product Performance Claims

API GL-4 / API GL-5

TRANSMAX Universal 80W-90

13 Dec 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890
www.castrol.com.au www.msds.castrol.com.au