



React Performance DOT 4

Super DOT4 brake fluid.

Description

Castrol React Performance DOT 4 is a high boiling synthetic brake fluid which far exceeds the requirements of the SAE J1704, FMVSS 116 DOT 3 and DOT 4, ISO 4925 and JIS K2233 specifications. This product has been formulated from mixed polyalkylene glycol ethers and borate ester together with other high performance additives and inhibitors which give ultimate system protection against the effects of corrosion and high temperature vapour lock.

Castrol React Performance DOT 4 brake fluid is designed for use in all brake systems particularly those which are exposed to extreme conditions such as high performance vehicles and race conditions.

Application

Castrol React Performance DOT 4 brake fluid has been specifically designed to be a high temperature alternative to DOT 5.1 fluids. Its superior characteristics give added benefit in situations where extreme conditions are encountered and ultimate braking response required. Castrol React Performance DOT 4 brake fluid is based on glycol ether and borate ester technology and as such has a high vapour lock point (measurement relating to high temperature performance under braking conditions). Because of the nature of this formulation, the vapour lock point can be sustained at a higher level than conventional glycol ether based fluids during the service life of the product.

Castrol React Performance DOT 4 brake fluid is specially engineered to cater for continuous start stop braking under city driving conditions, fast driving and hilly terrain where higher brake temperatures can be generated.

It is fully compatible with other fluids meeting FMVSS 116 DOT 3, DOT 4 and DOT 5.1 - however, in order to maintain the superior performance characteristics of Castrol React Performance DOT4 avoid mixing with other brake fluid products.

All conventional brake fluids deteriorate during use.

It is strongly recommended that Castrol React Performance DOT 4 should be changed according to the vehicle manufacturers advice. In the absence of such advice, a 2 year change period is recommended.

Conditions of Use

Castrol React Performance DOT 4 brake fluid should not be used in braking systems for which a mineral oil based fluid is recommended (for example, some Citroen systems, for which Castrol LHM is suitable and Rolls Royce systems, for which Castrol HSMO Plus is approved).

As with all brake fluids which contain glycol ethers, care should be taken to avoid spilling this product on paintwork, as it may have a damaging effect. In case of spillage, rinse the affected area with water immediately: Do not wipe.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Typical Characteristics

Name	Method	Units	Castrol React Performance DOT 4
Viscosity, Kinematic -40C	IP 71	mm ² /s	1200 typical
Density @ 20C	IP 160	g/ml	1.07
Wet Equilibrium Reflux Boiling Point	SAE J1703	°C	180 min
ERBP (Equilibrium Reflux Boiling Point)	ASTM D1120	°C	260 min
Appearance	Visual	-	Clear & Bright, yellow liquid
pH	SAE J1703	pH	7.2

Product Performance Claims

FMVSS 116 - DOT 4
ISO 4925 Class 4
JASO JIS K2233
SAE J1703
SAE J1704
AS 1960.1-2005 Grade 3

React Performance DOT 4
03 Sep 2019
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP-Castrol (Thailand) Limited, 3 South Sathon Road, Yannawa, Sathon, Bangkok 10120, Thailand
Technical Advice Line: 662 684 3591 Customer Service: 662 684 3555
www.castrol.com