



Transmax Limited Slip 80W-90

Axle Fluid for limited slip differentials

Description

Castrol Transmax Limited Slip 80W-90 is a mineral oil based gear oil which is suitable for use in limited slip differentials in cars and commercial vehicles where API GL-5 oils with specific limited slip friction performance is required. It can also be used in conventional differentials.

Advantages

- Optimised and stable friction characteristics for effective operation of limited slip differentials throughout the drain interval.
- Very good wear protection, even under severe conditions, prolongs component life.

Typical Characteristics

Name	Method	Units	Transmax Limited Slip 80W-90
Density @ 15 °C, Relative	ASTM D4502	g/ml	0.885
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.5
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	139
Viscosity Index	ASTM D2270	None	98
Viscosity, Brookfield @ -26C (80W)	ASTM D2983	mPa.s (cP)	140000
Pour Point	ASTM D97	°C	-33
Flash Point, COC	ASTM D92	°C	220

Product Performance Claims

API GL-5
Limited Slip Performance

Transmax Limited Slip 80W-90
09 Sep 2020
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Middle East, Standard Chartered Tower, 8th Floor, Down Town Burj Khalifa, By Emaar Square, P.O. Box 1699, Dubai, United Arab Emirates
Technical / Customer Service: +9714-3317999
www.bp.com