

## 30 Inch TimeMaster™, Model No. 21200



### **TECHNICAL SPECIFICATIONS AND FEATURES**

<b>Engine</b>	Briggs & Stratton 1000™ Pro Series 223 cc single cylinder engine with electric starter. 13.6 Nm (10.0 ft-lbs) Gross Torque (rated at 2800 rpm as per SAE J1940). Also, the engine is equipped with top mounted recoil starter.
<b>Housing</b>	Die cast aluminum frame with stamped steel cutting chamber.
<b>Height Of Cut</b>	Two adjustment points, one for the front wheels and a rear point for the rear wheels. Seven positions front and rear ranging from approximately 31.7 mm to 108.0 mm (1.25 to 4.25 inch).
<b>Blades</b>	Two 39.1 cm (15.4 in) long Atomic Hi-lift (standard), heat-treated alloy steel blades. Tip Speed: 17,980 fpm @ 3,300 +/- rpm.
<b>Controls</b>	Throttle Control: None, fixed engine speed at 3,400 +/- 100 rpm (blades not engaged). Personal pace control handle with control bail and secondary lock-out for BBC system. Blade Brake Control (BBC) – lockout lever and control bail releases mechanical blade brake. Control Handle: two operating positions 99.1 cm (39.0 inches) and 117.6 cm (44.0 inches) heights. Two storage positions (vertical and horizontal). Recoil and Electric start with key switch with off/on and momentary start.
<b>Wheels</b>	Front - 20.3 cm x 5.7 cm (8.0 inch x 2.25 inch) Toro grey with semi-pneumatic tyre with brick-like tread design. Rear - 25.0 cm x 7.6 cm (10.0 inch x 3.0 inch) Toro grey with semi-pneumatic tyre with brick-like tread design. All wheels have two precision ball bearings.
<b>Catching Bag</b>	88.1 litres (2.5 Bushels).
<b>Gearbox</b>	General Transmissions, sealed single reduction gearbox with bevel gears, cone clutch design, with die cast aluminum housing, splash oil lubricated. Ground Speed: 8.1 km/h (5.0 mph) – calculated.
<b>Width:</b>	81.3 cm (32.0 inches) – Mid HOC, highest handle setting.
<b>Length</b>	165.1 cm (65.0 inches) – Mid HOC, highest handle setting.
<b>Height</b>	117.8 cm (44.0 inches) – Mid HOC, highest handle setting.
<b>Fuel Tank Capacity</b>	1.14 litres.
<b>Shipping Weight</b>	74.2 kgs (167.0 lbs).
<b>Warranty</b>	Residential: 3 years mower, 2 years GTS, 2 years engine. Commercial: 45 days mower, N/A GTS, 90 days engine. <b>NOTE:</b> Engine warranty is through Briggs and Stratton Australia (Ph No. 1300 274 447).

**For additional technical and servicing information regarding this mower refer to Service Bulletins WBMSB 04/12, issued 20 July 2012 and WBMSB 02/17, issued November 3, 2017.**

**ACCESSORIES AND ATTACHMENTS:**

Product	Part No.
30 inch Walk Behind Mower Cover	490-7461
Lawn Striper Kit	20602

**REGULAR MAINTANENCE ITEMS**

Product	Part No.
Air Cleaner Cartridge	Briggs & Stratton P/No. 795066
Air Cleaner Pre-Cleaner (Foam) Element	Briggs & Stratton P/No. 796254
Spark Plug	Champion RC14YC
In-Line Fuel Filter	Briggs & Stratton P/No. 691035
Engine Oil Type	Detergent 4-stroke engine oil, API service classification SJ or higher. Viscosity: SAE 30 or 10W-30
Engine Oil Capacity	0.54 to 0.59 litre (18.0 to 20.0 ounces)

**Service Parts**

Product	Part No.
Spindle Assembly	120-6234
Spindle Shaft - RH	120-5234
Spindle Shaft - LH	120-5235
Spindle Bearings (2 per spindle)	38-7820
Blade Adaptor	120-5236
Synchronous Belt	120-3335
Synchronous Belt Sprocket	121-9100
Synchronous Belt Idler Kit	131-4529
Brake Arm Belt Idler	120-7082
Blade Attaching Bolt	125-2466
V-Belt (BBC)	121-5765
V-Belt (Traction)	120-9470
Front Wheel Assembly	125-2510
Rear Wheel Assembly	125-2509
Pinion Gear (15T)	131-5399
BBC Brake Cable	133-1998
Traction Cable	127-6867
Deck Washout Port Fitting	133-9289
Grass Bag	121-5770
Battery	106-8397
Ignition Key	700918
Battery Charger	BC12V
Side Discharge Chute	121-2319
Side Deflector (for Service)	133-2630

**Blade Types**

Blade Type	Part No.
Replacement Blade (2 required) – 15.4 in. Atomic Mulch Hi-lift (standard fitment)	116-6358-03
Replacement Blade (2 required) – 15.4 in. Atomic Mulch Medium-lift (optional)	120-9500-03