

## 60V 56 cm Recycler® Lawn Mower, Model No. 21864



### TECHNICAL SPECIFICATIONS AND FEATURES

<b>Motor</b>	Brushless 60 volt. 2 kW DC motor. Powered by a 6.0 Ah, 60-volt battery (standard). Runtime 40 minutes, with charge time 150 minutes.
<b>Housing</b>	Stamped steel, spiral grass chamber with rear bagging, side discharge and recycling (mulching) capability. Includes front throw baffle, and rear discharge opening with spring loaded door. Side discharge is via optional discharge chute P/No. 139-6556.
<b>Height of Cut</b>	Each wheel individually adjustable by leaf spring type hand levers, from 2.5 cm to 10.2 cm (1.0 to 4.0 inches), nine positions, in approximately 0.85 cm (0.3 inch) increments.
<b>Blade</b>	55.2 cm long heat-treated alloy steel. Triangle serrated style blade is attached to motor shaft with a blade driver, blade retainer, and special bolt with lock washer.
<b>Controls</b>	Blade Brake Bail: With bail against the upper handle, motor can be started and run (with button depressed at start switch). With the bail released, the motor will stop. Self-Propel Bail: The telescopic control handle converts sliding motion to rotary motion, engaging the transmission cable. Infinitely variable ground speed is determined by the relative position of the telescopic control handle, which is controlled by the operator's walking speed. Handle has SmartStow capability.
<b>Wheels</b>	<b>Front:</b> 20.3 x 5.7 cm (8.0 x 2.25 inch) – Grey Hub with Monprene tread tyre. <b>Rear:</b> 24.1 x 5.7 cm (9.5 x 2.25 inch) – Grey Hub with Monprene tread tyre.
<b>Cutting/Catching Bag</b>	Grass cutting on a single charge: 1335.4 m <sup>2</sup> (0.33 acre). Bag volume: 63.4 litres (1.8 bushels).
<b>Gearbox</b>	Rear wheel drive maintenance free gearbox with a 5.25:1 final drive ratio. Enclosed over-running ratchet clutches that provide positive forward drive and a differential action. Adjustable traction cable pivots the gearbox to tighten or loosen the drive belt for clutching function. Ground speed is infinitely variable from 0 to 7.2 km/h (0 to 4.5 mph) with push-to-propel system.
<b>Width:</b>	59.0 cm (23.2 inches).
<b>Length</b>	158.2 cm (62.3 inches) – control handle in lowest operating position.
<b>Height</b>	104.1 cm (41.0 inches). – low HOC, and control handle in lowest operating position, blade brake bail engaged.
<b>Weight</b>	43.1 kgs (95.0 lbs.).
<b>Warranty</b>	Residential Use: 3 years. Commercial Use: 30 days. <i>For all other conditions, refer to the online The Toro Warranty statement.</i>

Any specifications and dimensions in this Specs & Spares release are subject to change without notice and without incurring any obligation.

**For additional technical and servicing information regarding this mower refer to Service Bulletin WBMSB 03/22.**

*Issue Date: April 8, 2022*

**PLEASE NOTE:** The Toro Part Numbers quoted are correct at the time of this Specs & Spares release. Always refer to the appropriate Parts Manual based upon the machine's serial number to ensure correct parts availability and fitment.

### **ACCESSORIES AND ATTACHMENTS**

<b>Product</b>	<b>Part No.</b>
Side Discharge Chute Assembly	139-6556
Lawn Striping Kit with 22-inch Roller	20601
Toro Smart Stow Walk Mower Cover	490-2012
Toro Small Walk Behind Bag	490-7318
60 V Battery Charger (2 Amp CE)	81802
60 V 2.5 AH Battery CE	81802
60 V 4.0 AH Battery CE	81850
60 V 7.5 AH Battery CE	81875

### **MAINTANENCE ITEMS**

<b>Product</b>	<b>Part No.</b>	<b>Product</b>	<b>Part No.</b>
Transmission Drive Belt	140-4041	Traction Control Cable	139-6595
Height of Cut Lever Knob	110-0549	Brake Control Cable	139-6594
Grass Bag (without frame)	139-5471	Blade Support	108-3766-03
Handle Quick Release Assembly	138-3249	Blade Driver	139-1816
Front Wheel Assembly	140-2355	Blade Attaching Bolt	125-2466
Rear Wheel Assembly	140-2350	Trailing Shield	139-6597
Start Switch Assembly	144-3179	Standard 60 V 6.0 AH Battery CE	81860

### **Blade Type**

<b>Blade Type</b>	<b>Part No.</b>
Standard Replacement Blade	144-3177-03