

# TimeCutter<sup>®</sup> MX 5075, Model No. 75755TA



## TECHNICAL SPECIFICATIONS AND FEATURES

<b>Engine</b>	Toro LC2P77F, Spec 139-0602 (original), 139-0603 (service), 18.3 kW (24.5 hp), 708 cc, overhead valve, V-twin (cast iron sleeves) single camshaft, air cooled engine with full pressure lubrication and full flow oil filter. High idle speed set at 3,300 +/- 100 rpm.
<b>Construction</b>	Riveted and bolted 10-gauge steel.
<b>Deck Size</b>	127.0 cm (50.0 inch).
<b>Deck Configuration</b>	Right side discharge, three blade mid-mounted rotary. Fabricated 10-gauge steel housing with welded reinforcements, mounting brackets, and gauge wheel brackets. Frame supported. Left, centre and right front mounted anti-scalp rollers with four height positions.
<b>Deck Spindles</b>	Die cast aluminum spindle housing (3). Permanently lubricated precision ball bearings. 17.0 mm (0.66inch) diameter spindle shaft.
<b>Height of Cut</b>	3.8 cm to 11.4 cm (1.5 to 4.5 inches) HOC in 7 increments.
<b>Hydro Drive Unit</b>	Dual Hydro-gear ZT-2200 hydrostatic transaxles, belt drive with self-tensioning system.
<b>Ground Speed</b>	Mow: 0 to 11.3 km/h (0 to 7.0 mph). Trim: 0 to 8.9 km/h (0 to 5.5 mph). Tow: 0 to 6.4 km/h (0 to 4.0 mph). Reverse: 0 to 4.4 km/h (0 to 3.5 mph).
<b>Wheel Base</b>	115.8 cm (45.6 inches) – centre of rear tyre to centre of front tyre.
<b>Steering Control</b>	Ergonomic, adjustable steering levers with dampeners.
<b>Width</b>	<b>Deflector Down:</b> 156.2 cm (61.5 inches). <b>Deflector Up:</b> 129.5 cm (51.0 inches).
<b>Overall Length</b>	190.0 cm (75.0 inches) – rear bumper to front edge of caster wheel.
<b>Overall Height</b>	
<b>Tyres</b>	Front - 11 /600-5, 4 ply rated, smooth tread, pneumatic. Rear - 18 x 9.5-8, 4 ply rated, turf tread, pneumatic.
<b>Fuel Tank Capacity</b>	11.4 litres (single tank).
<b>Net Weight</b>	287.6 kg (634.0 lbs.).
<b>Seat</b>	45.7 cm (18 inch) handcrafted high back contoured seat with large bolsters and thick cushion. Standard with pivotable armrests. Seat pan is fastened to MyRIDE suspension platform.
<b>Warranty</b>	<b>Consumer:</b> Machine 3 years, Engine & Transaxles 3 years, Wear Parts 90 days, Battery: 1 year (first 90 days parts and labour, balance of year (91-365 days) parts only). <b>Commercial:</b> Machine & Transaxles 30 days, Engine 3 year/300 hours (whichever occurs first), Wear Parts 90 days, Battery: 30 days. <b>Attachments:</b> 1 year. <i>For all other conditions, refer to the online The Toro Warranty statement.</i>

Any specifications and dimensions in this Specs & Spares release are subject to change without notice and without incurring any obligation.

**For additional technical and servicing information regarding this mower, refer to Service Bulletin TCSB02-20, issued August 28, 2020.**

**PLEASE NOTE:** The Toro Part Numbers quoted are correct at the time of this Specs & Spares release. Always refer to the appropriate Parts Manual based upon the machine's serial number to ensure correct parts availability and fitment.

## ACCESSORIES AND ATTACHMENTS

Product	Part No.
Twin Bagger Kit	79412
Bagging Enhancement Kit	139-7459
Hour meter Kit	116-5461
Recycler Kit	139-3240
Deck Maintenance Jack#	127-6666
Jack Mount Kit	140-2711
LED Light Kit	140-2056
ROPS Kit	79485
MyRIDE Heavy Duty Spring Kit	140-2051
Seat Cover (with armrests)	117-0097
Storage Cover	490-7516

# Jack requires mount kit 140-2711.

Product	Part No.
Striping Kit	121-5706, or 140-5160
Heavy Duty Air Cleaner Kit***	135-6195
Assist Bar	140-2052
Sunshade Kit	140-2054
Floormat Kit	140-2061
Slope Sensor Kit	79486
Toro Standard V-Twin Maintenance Kit	139-0646
Toro H/Duty V-Twin Maintenance Kit	139-0649

\*\*\* Highly recommended if machine is fitted with a bagger attachment.

## REGULAR MAINTANENCE ITEMS

Product	Part No.
Air Cleaner Element Complete	136-7806
Air Cleaner Foam Element	136-7804
H/Duty Air Cleaner Element	108-3811
Engine Oil Filter	136-7848
Engine Fuel Filter	133-1563
Spark Plugs	Champion® RN9YC or NGK® BPR6ES
Engine Valve Cover Gasket	127-9295 (2 required)

Product	Type / Capacity
Engine Oil Type	Detergent engine oil, API service SF, SG, SH, SJ or SL. Engine Oil SAE-30 for normal conditions – otherwise refer to Operator's Manual.
Engine Oil Capacity	Without oil filter change – 2.3 litres With oil filter change – 2.4 litres
Transaxle Oil	SAE 20W-50 API Engine Oil
Transaxle Oil Capacity	1.6 to 1.65 litres per side

Product	Part No.	Product	Part No.
Traction Drive Assembly Drive Belt	139-2399	Deck Plastic Discharge Deflector	138-7502
Traction Drive Assembly Flat Idler Pulley	138-7597	Deck Washout Port Fitting	133-9289
Traction Drive Assembly Idler Pulley	68-0030	Deck Anti-Scalp Roller	1-603299
Traction Drive Assembly Engine Pulley	138-9792	Blade Attaching Screw	26-0671
Transaxle Pulley and Fan Kit	135-7349	Blade Attaching Screw Washer	3290-465
PTO Clutch	127-3408	Fuel Tank Cap	137-4119
Deck Spindle Housing	139-3214	Caster Wheel Tyre	138-7553
Deck Spindle Drive Belt	119-8820	Rear Tyre	140-2731
Deck Spindle Pulley	139-7454	Ignition Key	63-8360
Deck Spindle Drive Belt Flat Idler Pulley	132-9420	Battery (Dry)	105-1692
Deck Spindle Shaft	117-7268	Throttle Cable	139-2403
Deck Spindle Bearing (2 required)	138-9770	Choke Cable	139-2402
Deck Drive Belt Cover	139-3293		

## Blades

Blade Type	Part No.	Blade Type	Part No.
Standard and Bagger Application (Hi-Lift)	115-5059-03	Optional (Recycler / Mulch)	115-5062-03