



Count on it.

# TimeCutter® MX3400, Model No. 75730TA



## TECHNICAL SPECIFICATIONS AND FEATURES

<b>Engine</b>	Kawasaki FR600V-_S04-R, 13.4 kW (18.0 hp) (as per J1995), 603 cc, overhead valve, V-twin, single camshaft, air cooled engine with full pressure lubrication and full flow oil filter. High idle speed set at 3,300 +/-100 rpm. Standard Kawasaki style paper air cleaner fitted.
<b>Construction</b>	Riveted and bolted 10 gauge steel.
<b>Deck Size</b>	86.4 cm (34.0 inch).
<b>Deck Configuration</b>	Right side discharge, two blade cantered mid-mounted rotary. Fabricated 10 gauge steel deck with welded reinforcements, mounting brackets and gauge wheel brackets. Frame supported. Left and right front mounted anti-scalp rollers with four height positions.
<b>Deck Spindles</b>	Die cast aluminum spindle housing (2). Permanently lubricated sealed precision ball bearings. 17.0 mm (0.66inch) diameter spindle shaft.
<b>Height of Cut</b>	3.8 cm to 11.4 cm (1.5 to 4.5 inches) HOC in 7 increments.
<b>Hydro Drive Unit</b>	Dual Hydro-gear ZT-2100 hydrostatic transaxles, belt drive with self-tensioning system.
<b>Ground Speed</b>	Mow: 0 to 11.3 km/h (0 to 7.0 mph). Trim: 0 to 8.9 km/h (0 to 5.5 mph). Tow: 0 to 6.4 km/h (0 to 4.0 mph). Reverse: 0 to 4.4 km/h (0 to 3.5 mph).
<b>Wheel Base</b>	115.8 cm (45.6 inches) – centre of rear tyre to centre of front tyre.
<b>Steering Control</b>	Ergonomic, adjustable steering levers with heavy-duty dampeners.
<b>Width</b>	<b>Deflector Down:</b> 114.3 cm (45.0 inches). <b>Deflector Up:</b> 104.1 cm (41.0 inches).
<b>Overall Length</b>	190.5 cm (75.0 inches)
<b>Overall Height</b>	97.0 cm (38.2 inches).
<b>Tyres</b>	Front - 11 x 4.0-5.0, 2 ply, smooth tread, pneumatic. Rear - 18 x 6.0-8, 2 ply, super turf tread, pneumatic.
<b>Fuel Tank Capacity</b>	11.4 litres (single tank).
<b>Net Weight</b>	242.2 kg (534.0 lbs.).
<b>Seat</b>	40.67 cm (16.0 inch) handcrafted contoured seat, adjustable, hinged mounting, with spring suspension.
<b>Warranty</b>	<b>Residential:</b> Machine 3 years, Engine & Transaxles 3 years, Wear Parts (including belts & tyres) 90 days, Battery: 1 year (first 90 days parts and labour, balance of year (91-365 days) parts only). <b>Commercial:</b> Machine & Transaxles 30 days, Engine 3 years, Wear Parts (including belts & tyres) 90 days, Battery: 30 days. <b>Attachments:</b> 1 year. <b>NOTE:</b> Engine warranty is through Kawasaki USA, but administered by Toro Australia. <i>For all other conditions, refer to The Toro Warranty statement accompanying the machine.</i>

Any specifications and dimensions in this Specs & Spares release are subject to change without notice and without incurring any obligation.

**For additional technical and servicing information regarding this mower, refer to Service Bulletin TCSB01-21, issued April 9, 2021.**

Issue Date: April 9, 2021

**PLEASE NOTE:** The Toro Part Numbers quoted are correct at the time of this Specs & Spares release. Always refer to the appropriate Parts Manual based upon the machine's serial number to ensure correct parts availability and fitment.

### **ACCESSORIES AND ATTACHMENTS**

Product	Part No.
Twin Bagger Kit - 34 inch	79417
Blowout Ring Kit	140-8369
Recycler Kit – 34 inch	140-3536
Hourmeter Kit	116-5461
ROPS Kit	79485
Slope Sensor Kit, TimeCutter	79486
Deck Maintenance Jack #	127-6666
Jack Mount Kit	140-2711
LED Light Kit	140-2056

# Jack requires mount kit 140-2711 and cannot be used if Assist Bar Kit 140-2952 is fitted.

Product	Part No.
Deck Foot Lift Assist Kit	140-2059
Floor Mat Kit	140-2060
Seat Armrest Kit	140-2058
Seat Cover (W/O armrests)	117-0096
Assist Bar Kit	140-2052
Sunshade Kit	140-2054
Storage Cover	490-7516
Striping Kit – 34 inch	140-8374
Front Weight Kit	140-2050
Deluxe Seat Kit	140-2057

### **REGULAR MAINTANENCE ITEMS**

Product	Part No.
Air Cleaner Element	11013-0727
Engine Oil Filter	49065-0721
Engine Fuel Filter	49019-0031
Rocker Cover Gasket (2 required)	119-5805, or 11061-7083
Spark Plugs (2 required)	NGK BPR4ES

Product	Type / Capacity
Engine Oil Type	Detergent engine oil, API service SJ or higher. Engine Oil SAE 10W-40 or 20W-50 for normal conditions – otherwise refer to Operator's Manual.
Engine Oil Capacity	Without oil filter change – 1.5 litres With oil filter change – 1.7 litres
Transaxle Oil	SAE 20W-50 API Engine Oil
Transaxle Oil Capacity	1.6 to 1.65 litres per side

Product	Part No.	Product	Part No.
Traction Drive Assembly Drive Belt	139-2399	Deck Plastic Discharge Deflector	140-3548
Traction Drive Assembly Flat Idler Pulley	138-7597	Deck Washout Port Fitting	133-9289
Traction Drive Assembly Idler Pulley	68-0030-03	Deck Anti-Scalp Roller	1-603299
Traction Drive Assembly Engine Pulley	138-9792	Blade Attaching Screw	26-0671
Transaxle Pulley and Fan Kit	135-7349	Blade Attaching Screw Washer	3290-465
PTO Clutch	117-7468	Fuel Tank Cap	137-4119
Deck Spindle Housing	139-3214	Caster Wheel Tyre	140-2736
Deck Spindle Drive Belt	140-5141	Rear Tyre	140-5129
Deck Spindle Pulley	127-0098	Ignition Key	63-8360
Deck Spindle Drive Belt Flat Idler Pulley	132-9420	Battery (Dry)	105-1692
Deck Spindle Shaft	117-7268	Throttle Cable	139-2403
Deck Spindle Bearing (2 required)	138-9770	Choke Cable	139-2402
Deck Belt Cover	144-1905		

### **Blades**

Blade Type	Part No.
Standard – all applications (Bagging / Recycler / Mulch)	140-5134-03