

## TimeCutter® MX4225, Model No. 75746TA



### TECHNICAL SPECIFICATIONS AND FEATURES

<b>Engine</b>	Kohler KT725-3097 16.4 kW (22.0 hp) as per J1940, 725 cc, overhead valve, V-twin single camshaft, air cooled engine with full pressure lubrication and full flow oil filter. Standard Kohler paper element air cleaner.
<b>Construction</b>	Riveted 10 gauge steel.
<b>Deck Size</b>	106.7 cm (42.0 inch).
<b>Deck Configuration</b>	Right side discharge, mid mounted rotary. Fabricated 10 gauge steel deck with welded reinforcements, mounting brackets and gauge wheel brackets. Frame supported. Left and right front mounted anti-scalp rollers with four height positions.
<b>Deck Spindles</b>	Die cast aluminum spindle housing (2). Permanently lubricated sealed precision ball bearings. 17.0 mm (0.66inch) diameter spindle shaft.
<b>Height of Cut</b>	3.8 cm to 11.4 cm (1.5 to 4.5 inches), adjusts in seven increments.
<b>Hydro Drive Unit</b>	Dual Hydro-gear ZT-2100 hydrostatic transaxles, belt drive with self-tensioning system.
<b>Ground Speed</b>	High: 0 to 11.3 km/h (0 to 7.0 mph). Medium: 0 to 8.9 km/h (0 to 5.5 mph). Low: 0 to 6.4 km/h (0 to 4.0 mph). Reverse: 0 to 4.4 km/h (0 to 3.5 mph).
<b>Wheel Base</b>	115.8 cm (45.6 inches) – centre of rear tyre to centre of front tyre.
<b>Steering Control</b>	Ergonomic, adjustable steering levers with heavy-duty dampeners.
<b>Width</b>	<b>Deflector Down:</b> 134.6 cm (53.0 inches). <b>Deflector Up:</b> 123.2 cm (48.5 inches).
<b>Overall Length</b>	185.4 cm (73.0 inches).
<b>Overall Height</b>	97.0 cm (38.2 inches).
<b>Tyres</b>	Front – 11 x 4.00-5, 2 ply, smooth tread, pneumatic. Rear - 18 x 7.5-8, 4 ply, turf tread, pneumatic.
<b>Fuel Tank Capacity</b>	11.4 litres (single tank).
<b>Net Weight</b>	244.5 kg (539.0 lbs.) - estimated
<b>Seat</b>	40.67 cm (16.0 inch) handcrafted contoured seat, adjustable, hinged mounting, with spring suspension.
<b>Warranty</b>	<b>Residential:</b> Machine 3 years, Engine & Transaxles 3 years, Wear Parts (including belts & tyres) 90 days, Battery: 1 year (first 90 days parts and labour, balance of year (91-365 days) parts only). <b>Commercial:</b> Machine & Transaxles 30 days, Engine 3 years, Wear Parts (including belts & tyres) 90 days, Battery: 30 days. <b>Attachments:</b> 1 year. <b>NOTE:</b> Engine warranty is through Engineered Products Group (EPG) (Ph No. 1800 620 652). <i>For all other conditions, refer to The Toro Warranty statement accompanying the machine.</i>

Any specifications and dimensions in this Specs & Spares release are subject to change without notice and without incurring any obligation.

**For additional technical and servicing information regarding this mower, refer to Service Bulletin TCSB01-21, issued April 9, 2021.**

**PLEASE NOTE:** The Toro Part Numbers quoted are correct at the time of this Specs & Spares release. Always refer to the appropriate Parts Manual based upon the machine's serial number to ensure correct parts availability and fitment.

## **ACCESSORIES AND ATTACHMENTS**

Product	Part No.
Twin Bagger Kit	79411
Bagging Enhancement Kit	139-7478
Hourmeter Kit	116-5461
Recycler Kit	139-3265
Deck Maintenance Jack #	127-6666
Jack Mount Kit	140-2711
LED Light Kit	140-2056
ROPS Kit	79485
Seat Cover (without armrests)	117-0096

# Jack requires mount kit 140-2711 and cannot be used if Assist Bar Kit 140-2952 is fitted.

Product	Part No.
Storage Cover	490-7516
Striping Kit	140-5159
Assist Bar Kit	140-2052
Sunshade Kit	140-2054
Floormat Kit	140-2060
Slope Sensor Kit	79486
Deck Foot Assist Kit	140-2059
Front Weight Kit	140-2050
Deluxe Seat Kit	140-2057
Armrest Kit	140-2058

## **REGULAR MAINTANENCE ITEMS**

Product	Part No.
Air Cleaner Paper Element	32 083 09-S
Air Cleaner Foam Element (Optional)	32 08310-S
Engine Oil Filter	12 05001-S
Engine Fuel Filter	25 050 22-S
Spark Plugs	Champion® XC12YC

Product	Type / Capacity
Engine Oil Type	Detergent engine oil API service SJ or higher Engine Oil 10W-30 or SAE 30 for normal conditions – otherwise refer to Operator's Manual.
Engine Oil Capacity	1.7 litres without filter change 1.9 litres with filter change
Transaxle Oil	Toro HYPR-OIL 500 (preferable), or SAE 20W-50 API engine oil
Transaxle Oil Capacity	1.5 to 1.6 litres per side (approx.)

Product	Part No.	Product	Part No.
Traction Drive Assembly Drive Belt	139-2399	Deck Washout Port Fitting	133-9289
Traction Drive Assembly Flat Idler Pulley	138-7597	Deck Drive Belt Cover	144-1905
Traction Drive Assembly Idler Pulley	68-0030-03	Deck Anti-Scalp Roller	1-603299
Traction Drive Assembly Engine Pulley	138-9792	Blade Attaching Screw	26-0671
Transaxle Pulley and Fan Kit	135-7349	Blade Attaching Screw Washer	3290-465
PTO Clutch	117-7468	Fuel Tank Cap	137-4119
Deck Spindle Housing	139-3214	Caster Wheel Tyre	140-2736
Deck Spindle Drive Belt	119-8819	Rear Tyre	140-2729
Deck Spindle Pulley	139-2433	Ignition Key	63-8360
Deck Spindle Drive Belt Flat Idler Pulley	132-9420	Battery (Dry)	105-1692
Deck Spindle Shaft	117-7268	Throttle Cable	139-3267
Deck Spindle Bearing (2 required)	138-9770	Choke Cable	139-2402
Deck Plastic Discharge Deflector	138-7502		

## **Blade Types**

Blade Type	Part No.	Blade Type	Part No.
Standard and Bagger Application (Hi-Lift)	137-1999-03	Optional - (Recycler/Mulch)	117-5376-03